©COMMANDER™ XT™

HIGHLIGHTS

- Rotax® V-twin engine options
- Tri-Mode Dynamic Power Steering (DPS™)
- Visco-Lok‡ QE auto-locking front differential
- Double A-arm front suspension with dive-control geometry
- Torsional Trailing arm Independent (TTI) rear suspension with external sway bar
- Front sway bar
- Intelligent Throttle Control (iTC™)

- Industry's exclusive Dual-Level[™] cargo box
- 14-in. cast-aluminum wheels with 27-in. Maxxis Bighorn 2.0[†] tires
- 4,500-lb (2,041 kg) winch
- · Heavy-duty front bumper
- Rugged bed rails
- Mudguards
- Analog / Digital gauge



Boreal Green

ENGINES	1000R
Туре	92 hp, Rotax® 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC) with Electronic Fuel Injection (EFI)
Transmission	CVT, L / H / N / R / P, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS		
Front Suspension	Double A-arm with sway bar 10 in. (25.4 cm) travel	
Front Shocks	Twin tube gas charged shocks	
Rear Suspension	Torsional Trailing arm Independen (TTI) with external sway bar 10 in. (25.4 cm) travel	
Rear Shocks	Twin tube gas charged shocks	

BRAKES		
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper	

TIRES / WHEELS	S
Front Tires	Maxxis Bighorn 2.0 27 x 9 x 14 in. (68.6 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0 27 x 11 x 14 in. (68.6 x 27.9 x 35.6 cm)
Wheels	14-in. (35.6 cm) cast-aluminum

DIMENSIONS / CAPACITIES		
LxWxH	120.2 x 62.5 x 72 in. (305.4 x 158.8 x 182.9 cm)	
Wheelbase	75.8 in. (192.4 cm)	
Ground Clearance	11 in. (27.9 cm)	
Dry Weight*	1,291.4 lb (586 kg)	
Rack Capacity	600 lb (272 kg) Dual-Level cargo box Upper level: 400 lb (181 kg) Lower level: 200 lb (91 kg)	
Storage Capacity	Total: 8.3 gal (31.6 L) Glove box: 4.5 gal (17.2 L) Under driver seat: 3.5 gal (13.1 L) (800R only) Center console: 0.3 gal (1.3 L)	
Towing Capacity	1,500 lb (680 kg)	
Fuel Capacity	10 gal (37.8 L)	

Multifunction Analog / Digital: Speedometer, tachometer, odometer, trip and hour	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off	Lighting	240 W from four 60-W projectors with tail lights / brake lights
4,500-lb (2,041 kg) winch with roller fairlead	Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
Heavy-duty front bumper, mudguards, bed rails		
	Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off 4,500-lb (2,041 kg) winch with roller fairlead	Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off 4,500-lb (2,041 kg) winch with roller fairlead Anti-theft System

WARRANTY	
Factory	2-year limited warranty



