## **©OUTLANDER™ MAX 450 / 570**

## **HIGHLIGHTS**

- Rotax® engine options
- Continuously Variable Transmission (CVT) with engine braking
- Double A-arm front suspension
- Torsional Trailing arm Independent (TTI) rear suspension
- 1,300-lb (590 kg) towing capacity
- 25-in. Carlisle† Trail Wolf tires
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Multifunction digital gauge
- Steel racks with LinQ<sup>™</sup> quick-attach accessory system and a combined 360 pounds (163.3 kg) capacity

- 2.9-gal (10.9 L) water-resistant rear compartment
- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips
- Raised floorboards



Orange

\*Also available in 2-passenger MAX configuration

ENGINES	450	570	
Туре	38 hp, Rotax 427 cc single cylinder, liquid cooled	48 hp, Rotax 570 cc V-twin, liquid cooled	
Fuel Delivery System	Electronic Fuel Injection (EFI)		
Transmission	CVT, P / R / N / H / L, standard engine braking		
Drive Train	Selectable 2WD / 4WD with Visco-Lok <sup>‡</sup> auto-locking front differential		
Power Steering	N/A		

SUSPENSIONS		
Front Suspension	Double A-arm 9 in. (22.9 cm) travel	
Front Shocks	0il	
Rear Suspension	Torsional Trailing arm Independent (TTI) 8.8 in. (22.4 cm) travel	
Rear Shocks	Oil	

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

· ·	•
TIRES / WHEE	ELS
Front Tires	Carlisle Trail Wolf 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Rear Tires	Carlisle Trail Wolf 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	12-in. steel

DIMENSIONS / CAPACITIES	
LxWxH	91 x 46 x 52.5 in. (231 x 116.8 x 133 cm)
Wheelbase	59 in. (149.9 cm)
<b>Ground Clearance</b>	10.5 in. (26.7 cm)
Seat Height	33.8 in. (85.8 cm)
Engine / Dry Weight*	450 / 715 lb (324 kg) 570 / 741 lb (336 kg)
Rack Capacity	Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg)
Storage Capacity	Rear: 2.9 gal (10.9 L)
Towing Capacity	1,300 lb (590 kg)
Fuel Capacity	5.4 gal (20.5 L)

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer, odometer,	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
	trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Lighting	70 W from dual 35-W front light / brake light
Winch	Prewired for available winch	Seat	Convertible Rack System (CRS)
Protection	N/A	Anti-theft System	N/A

WARRANTY	
Factory	2-year limited warranty

