©OUTLANDER™ PRO 450/570

HIGHLIGHTS

- · Rotax® engine options
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- 26-in. Carlisle ACT HD 6-ply tires
- 12-in. cast-aluminum wheels
- Double A-arm front suspension
- Torsional Trailing arm Independent (TTI) rear suspension
- Visco-Lok QE auto-locking front differential
- 1,300-lb (590 kg) towing capacity
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control

- Digitally Encoded Security System (D.E.S.S.)
- 500-W magneto
- Multifunction digital gauge
- Steel racks with LinQ quick-attach accessory system and a combined 360 pounds (163.3 kg)
- 2.9-gal (10.9 L) water-resistant rear compartment



Green

| ENGINES | 450 | 570 | |
|----------------------|--|--|--|
| Туре | 38 hp, Rotax 427 cc single cylinder, liquid cooled | 48 hp, Rotax 570 cc V-twin, liquid cooled | |
| Fuel Delivery System | Electronic Fuel Injection (EFI) | | |
| Transmission | CVT, P / R / N / H / L, standard engine braking | | |
| Drive Train | Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential | | |
| Power Steering | Tri-Mode Dynamic Power Steering (DPS) | | |

| SUSPENSIONS | |
|------------------|--|
| Front Suspension | Double A-arm 9 in. (22.9 cm) travel |
| Front Shocks | 0il |
| Rear Suspension | Torsional Trailing arm Independent (TTI) 8.8 in. (22 cm) travel |
| Rear Shocks | 0il |

| BRAKES | |
|--------|--|
| Front | Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers |
| Rear | Single 214 mm ventilated disc brake with hydraulic twin-piston caliper |

| TIRES / WHEEL | S |
|---------------|--|
| Front Tires | Carlisle† ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm) |
| Rear Tires | Carlisle† ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm) |
| Wheels | 12-in. cast-aluminum |

| DIMENSIONS / CAPACITIES | | |
|-------------------------|--|--|
| LxWxH | 83 x 46 x 49 in. (211 x 116.8 x 124 cm) | |
| Wheelbase | 51 in. (129.5 cm) | |
| Ground Clearance | 11.5 in. (29.2 cm) | |
| Seat Height | 33.8 in. (85.8 cm) | |
| Engine / Dry Weight* | 450: 678 lb (308 kg) 570: 704 lb (319 kg) | |
| Rack Capacity | Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg) | |
| Storage Capacity | Rear: 2.9 gal (10.9 L) | |
| Towing Capacity | 1,300 lb (590 kg) | |
| Fuel Capacity | 5.4 gal (20.5 L) | |

| FEATURE: | | | |
|------------|---|-------------------|--|
| Gauge | Multifunction digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, | Instrumentation | Lighter type DC Outlet in console, standard connect the back (15-A) |
| | clock | Lighting | 70 W from dual 35-W front light / brake light |
| | | Seat | Reinforced seat skin |
| Winch | Prewired for available winch | Anti-theft System | Digitally Encoded Security System (D.E.S.S.) |
| Protection | N/A | | |

| WARRANTY | | |
|----------|-------------------------|--|
| Factory | 2-year limited warranty | |



