SRENEGADE X° mr 1000R

HIGHLIGHTS

- Rotax[®] snorkeled V-Twin engine with relocated CVT intake and outlet
- Intelligent Throttle Control (iTC[™]) with riding ٠ modes
- Front and rear FOX[†] PODIUM[†] 1.5 QS3 ٠
- 30-in. ITP Cryptid[†] tires •
- 14-in. cast-aluminum beadlock wheels
- 3,000-lb (1,361 kg) WARN[†] winch with roller fairlead
- Front & central aluminum skid plate
- Heavy-duty front and rear bumpers Continuously Variable Transmission (CVT) with • Extra Low L-Gear
- · Aluminum taper-profile handlebar with grab handle, wind deflectors ans square pad
- Tri-Mode Dynamic Power Steering (DPS[™])

- Torsional Trailing arm Independent (TTI) rear suspension
- Mudguards

1000F

- Multifunction digital gauge
- · Painted plastics for premium look
- X-package coloration, graphics and seat cover



Gold, Black & Can-Am Red / 1000R Carbon Black & Sunburst Yellow / 1000R

TIRES / WHEELS	5
Front Tires	ITP Cryptid† 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Rear Tires	ITP Cryptid† 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Wheels	14-in. cast-aluminum beadlock

DIMENSIONS / C	APACITIES
LxWxH	83 x 50 x 56 in. (224 x 127 x 131 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	12.5 in. (31.8 cm)
Seat Height	36.75 in. (93.3 cm)
Dry Weight	991 lb (450 kg)
Rack Capacity	Rear: 35 lb (16 kg)
Storage Capacity	N/A
Towing Capacity	1,300 lb (590 kg)
Fuel Capacity	5.4 gal (20.5 L)

Туре	91 hp, Rotax 976 cc V-twin, snorkeled, liquid cooled		
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)		
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking		
Drive Train	Selectable 2WD / 4WD with Visco-Lok \mbox{QE}^{\ddagger} auto-locking front differential		
Power Steering	Tri-Mode Dynamic Power Steering (DPS)		
SUSPENSIONS			
Front Suspension	Arched double A-arm with front sway bar		
Front Shooka			

rione ouspension	Allohed double A drill with Holt Sway bar		
Front Shocks	FOX† PODIUM† 1.5 QS3		
Rear Suspension	Torsional Trailing arm Independent (TTI)		
Rear Shocks	FOX† PODIUM† 1.5 QS3		
BRAKES			
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers		
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers		

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	240 W from 4 fender mounted projector beam headlamps (60 W) with tail light / brake light
		Seat	Standard
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Front & rear bumpers Aluminum taper-profile handlebar with grab handle, wind deflectors and square pad Mudguards front & central aluminum skid plate		

WARRANTY			
Factory	6-months limited warranty		
Extended	Up to 36 months B.E.S.T. coverage		
pecifications, price, design, features, models o	ecreational Products Inc (BRP). All rights reserved. TM, ^e and the BRP logo are registered trademarks of BRP or its affiliates. Products are A by BRP US Inc. [*] Base model dry weight shown. ⁴ Visco-Lok is a trademark of GKN Viscodrive GmbH. ¹ All other trademarks are the property mers. Because of our ongoing commitment to product quality and innovation. BRP reserves the right at anytime to discontinue or change requipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety	BRI	

approximations, proc. design, reards, provide to equipment without human any obligation. How reports and a many many human transmission and a many many human transmission and any obligation. How reports and training information, see your dealer or, in U.S.A. call the AYX start instrument material and obligation. How reports and training information, see your dealer or, in U.S.A. call the AYX start instrument material and obligation. How reports and training information, see your dealer or, in U.S.A. call the AYX start instrument and any obligation. How reports and training information, see your dealer or, in U.S.A. call the AYX start instrument and any obligation. How reports and training information and start (Council at 1 (613) 739-1535 ext 227. AVX can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs of mit. New retrieve internation and training information and training



Can-AmOffroad.com